

It's not magic, it's engineering."

Product Specification

Product Name:	GenieBoard [®] 302
Description:	A universal dry flooring board that can be used as an alternative to poured screed, or multiple plywood and cement board layers. Connects with a 50mm shiplap joint, which is glued and fixed with 22mm screws or staples at 200mm centres along board joints.
Application:	Can be used directly under all flooring types and on top of all GenieMat [®] products in lightweight and heavyweight buildings.
Dimensions:	500 mm x 1500 mm (Overlap 50mm)
Coverage:	0.75 m ²
Thickness:	nom. 25mm
Board Weight:	29 kg/m ²
Technical Data	
Acoustic Performance: (ISO 10140-2:210 & ISO 10140-3:2010)	Shall be R_w (+C _{tr}) 65 (-10)dB, $L_{n,w}$ 50dB, and $\Delta L_{n,w}$ 29 dB when tested on bare 140mm concrete slab , no ceiling.
	+5dB for airborne sound, 12dB improvement on Part E impact Sound
Fire Rating: (EN 13501-1:2018)	A2fl-s1
Thermal Resistance:	0.07 (m²*K)/W
Thermal Conductivity:	0.30 W/(m*K)
Water vapour permeability: (EN 12086)	13μ when 0/50 (A, dry) under condition 23 12μ when 50/93 (C, wet) under condition 23
Maximum Point Load:	3kN A load area of at least 7850 mm ² . (Stamp \emptyset = 100 mm).


⁸ ^{arms} Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.







It's not magic, it's engineering."




© Pliteq Inc. 2025.

⁸ ^{arms} Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.







AROUND THE WORLD.

PLITEQ INC.

131 Royal Group Crescent Vaughan, ON L4H 1X9 Canada

4211, Yonge Street, Suite 404, Toronto, ON M2P 2A9 Canada

2015 Main St, Vancouver, BC V5T 3C2 Canada

T.+1 416 449 0049 info@pliteq.com www.pliteq.com

PLITEQ (DE) 251 Little Falls Drive Wilmington, DE 19808

19808 United States of America

PLITEQ (AZ) 11701 N. 132nd Drive Surprise, AZ 85379 United States of America

T.+1 480 805 5560 info@pliteq.com www.pliteq.com

PLITEQ MEXICO

Calz. Gral. Mariano Escobedo 476-piso 12 Chapultepec Morales, Anzures, Miguel Hidalgo, 11590 Ciudad de México, CDMX Mexico

T.+52 1 938 164 1551

PLITEQ (UK) LTD. Office 205, Orega High Holborn, 16 High Holborn, London, WC1V 6BX United Kingdom

T.+44 203 9846444 info@pliteq.co.uk www.pliteq.co.uk

PLITEQ BUILDING MATERIALS TRADING LLC.

European Business Centre Dubai Investment Park PO Box 473 512 United Arab Emirates

T. +971 4 567 4944 info@pliteq.ae www.pliteq.ae

PLITEQ ASIA PACIFC PTE LTD.

#19-13, 101 Cecil Street, Tong Eng Building, 069533 Singapore

T.+65 6813 2017 info@pliteq.sg www.pliteq.sg

PLITEQ AUSTRALIA PTY LTD.

72 York Street, South Melbourne, VIC, 3205 Australia

T.+61 3 9018 7696 info@pliteq.com.au www.pliteq.com.au

















© Pliteq Inc. 2025.

Image: Interpret and the second s