

It's not magic, it's engineering."

Product Specification

Product Name:	GenieMat FF05NP
Material:	Robust reduced sound transmission mat made from 94% recycled rubber content.
Description:	Designed to reduce the transmission of impact sound generated by footfall noise for various types of structures for both residential and commercial use. Can be used directly under screed or gypsum concrete in concrete, steel and wood construction.
Features and Benefits:	• Tested by 3rd party accredited laboratories to significantly reduce impact sound
	• Mould, bacteria, fungi, and water resistant
	Qualifies for LEED® points
	Easy to install and rolls out quickly
	Will not fail under high point loads
	CE Marked
Dimension:	Rollgood: 1.22 m wide, 9.14 m long (4' wide, 30' long)
Coverage:	11.15 m2 (120 ft²)
Thickness:	nom. 5 mm (4.5mm +/- 0.5mm) ($\frac{1}{8}$ ") (tolerances are pursuant to ISO 3302-1)
Roll Weight:	43 kg/roll (95 lb/roll)
Technical Data	
Reduction of Impact Sound Pressure Level:	ΔLw 25 dB (ISO 717-2)
Tensile Strength & Elongation at Break (ASTM D412)	≥ 0.7 N/mm2 ≥ 65%
Type A Hardness (ASTM D2240):	40 durometer

© Pliteq Inc. 2019. a °™ Trademarks of Pl

*^{*M} Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.






GENIEMAT[®] FF05NP Sound Control Underlayment



It's not magic, it's engineering."

Technical Data	
Temperature Stability:	-40°C to +115°C (-40°F to +240°F)
Thermal resistance (R-value):	0.038 (m²K)/W
Thermal transmittance (U-value):	26.6 W/(m ² K)



© Pliteq Inc. 2019.

^a^a → Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.







AROUND THE WORLD.



PLITEQ INC. 131 Royal Group Crescent Vaughan, ON L4H 1X9 Canada

T. + 1 416 449 0049

info@pliteq.com www.pliteq.com

PLITEQ (UK) LTD. Irongate House

22-30 Dukes Place London EC3A 7LP

T. + 44 203 9846444

info@pliteq.co.uk www.pliteq.co.uk

PLITEQ BUILDING

MATERIALS TRADING LLC. European Business Centre Dubai Investment Park PO Box 473 512 Dubai, UAE

T: +971 4 567 4944

info@pliteq.ae www.pliteq.ae

PLITEQ ASIA PACIFIC PTE LTD.

101 Cecil Street #19-13 **Tong Eng Building Singapore** 069533

T. +65 8452 6865

info@pliteq.sg www.pliteq.sg



© Pliteq Inc. [™] Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.